



**NOTES:**

**\*Material**

Housing:LCP+50%G.F., UL94V-0 Rated;Color:Black.  
 Shield: Brass.  
 Plating: Nickle(40~80u") Plating .  
 Contact: Brass.  
 Plating: Gold Plating Over Nickel(40~80u") on Contact Area; Tin(100~250u") Plating on Solder Tail.

**\*Electrical Specification**

Operation Voltage: 40 VAC max.  
 Current Rating: 0.5 Ampere per contact  
 Contact Resistance: 30 Milliohms max.  
 Insulation Resistance: 100 Megohms min.  
 Dielectric Withstanding Voltage: 500 VDC

**\*Environmental**

Operating Temperature: -20°C to +85°C

DISP-SWMNPC-20-LF  
 LEADFREE  
 RoHS Compliant



PART NO. DISP-SWMNPC-20

DWG NO. DISP-SWMNPC-20

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2  
 .XX ±  
 .XXX ±  
 AWG

DESCRIPTION:

DisplayPort Peceptacle (Female)  
 SMT Type(With Flange)

AREA

REVISIONS

HK

DATE

煜倫股份有限公司