



Specifications:
 Current Rating:1.0 Amp
 Contact resistance:20m Ohm Max. at 6V DC 0.3A
 Insulator resistance:1000M ohm min. at 500V DC
 Withstanding Voltage:500V AC/Minute
 Operating Temperature Range:-40°~+105°C
 Wire Size Flat Cable I.D.C: 1.27mm Pitch
 AWG#28(standard) OR #30 (solid).
 Material And Finish
 Insulator:PBT&Glass-fiber reinforced UL94V-0
 Insulator Color:Black
 Contact:Phosphor Bronze or Brass
 Contact Plating:See Contact Plating Tab.
 Note:(*)Marked is Important DIM For QC.

No. of Positions

| No. | A | B | C |
|-----|-------|-------|-------|
| 10 | 22.36 | 10.16 | 11.43 |
| 16 | 29.98 | 17.78 | 19.05 |
| 20 | 35.06 | 22.86 | 24.13 |
| 26 | 42.68 | 30.48 | 31.75 |
| 34 | 52.84 | 40.64 | 41.91 |
| 40 | 60.46 | 48.26 | 49.53 |
| 50 | 73.16 | 60.96 | 62.23 |

E-C2FE-xx-LF
 LEADFREE
 FE:FULL/EAR 10~50WAY
 RoHS Compliant

with whole circular hole Type



| | | | | | | | | |
|--------------------|-----------|---------------|--|--|--|-----------|----|------|
| PART NO. E-C2FE-xx | | CHECKED BY CY | | TOLERANCES ARE .X±0.2 .XX± .XXX± AWG | DESCRIPTION: 2545 2.54mm Pitch Card Edge | | | |
| DWG NO. E-C2FE-xx | | DRAWING BY | | | AREA | REVISIONS | HK | DATE |
| FILE NO. | | PROJECTION | | | | | | |
| UNIT / mm | SCALE 1:1 | | | | | | | |

煜倫股份有限公司