



CABLE	DIM
A	90±5
B	87±5
C	85±5
D	80±5
E	305±5
F	300±5
G	295±5
H	290±5

P	COLOR	P2	P3
1	WHITE	4	
	WHITE		4
2	WHITE	3	
	WHITE		3
3	WHITE	2	
	WHITE		2
4	WHITE	1	
	WHITE		1

Note: the above wire sizes do not include conn at both ends.

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #22 WHITE	1PCS	E108485
2	WIRE:	UL1007 #22 WHITE	1PCS	E108485
3	WIRE:	UL1007 #22 WHITE	1PCS	E108485
4	WIRE:	UL1007 #22 WHITE	1PCS	E108485
5	WIRE:	UL1007 #22 WHITE	1PCS	E108485
6	WIRE:	UL1007 #22 WHITE	1PCS	E108485
7	WIRE:	UL1007 #22 WHITE	1PCS	E108485
8	WIRE:	UL1007 #22 WHITE	1PCS	
9	HOUSING:	09-50-8041 (MOLEX)	3PCS	
10	TERMINAL:	08-50-0106 (MOLEX)	12PCS	
11	CABLE TIE:	NATURAL COLOR 2.5*100mm	4PCS	
12				

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG ±

PJECTION

照片框

ORDER INFORMATION

KKX12-0404RR22MX-F27C-LF

SERIES

LEADFREE

270mm

FEMALE TO FEMALE

MOLEX

22 AWG

04 TO 04 WAY 90°/90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y