



PC Board Layout

NOTES:  
ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS.
  2. CURRENT RATING : 1.5 AMP.
  3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
  4. INSULATION RESISTANCE: 500 MEGOHMS MIN @ 500 VDC.
  5. DIELECTRIC STRENGTH: 1000 VAC RMS 50Hz or 60Hz, 1MIN.
- MECHANICAL:
1. HOUSING & INSERT MATERIAL : PA46 UL94V-0.
  2. CONTACT MATERIAL: DIAMETER 0.45MM PHOSPHOR BRONZE  
GOLD PLATING OVER NICKEL.
  3. SHIELD: 0.20 ~ 0.25MM THICKNESS BRASS WITH NICKEL PLATED
  4. MATING/UNMATING FORCE: 2.2KG. F MAX.
  5. RETENTION STRENGTH: 7.7KG. F MIN BETWEEN JACK AND PLUG.
  6. OPERATING LIFE: 750 CYCLES MIN.

ENVIRONMENTAL:

1. STORAGE: -40° C ~ +85° C RELATIVE HUMIDITY <70%
2. OPERATION: 40° C ~ +85° C

Remark:

The mark with ★ is the key inspection dimension for QC

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY		X. ± .X ± 0.25 .XX ± 0.15 .XXX ± 0.05 ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	P PROJECTION	

照片框

ORDER INFORMATION

MJF13S-KX06B3-0808-LF			
SERIES		8P8C	LEADFREE
BLACK	06u" GOLD	REAR TAB 3.05mm	NON EAR

DESCRIPTION: